



## Sunset Select Matte Canvas

LexJet's Sunset Select Matte Canvas offers users a high-quality, water-resistant poly cotton-blend canvas with an unsurpassed white point. This new pH neutral, acid-free inkjet coating allows for greater consistency from print to print. It creates the perfect medium for fine art printers and photographers alike, truly making it the perfect vehicle for artist reproductions of the highest order. This material can be stretched, mounted, or finished with grommets.

Property	Specifications
Material	35% Cotton, 65% Polyester Blend
Gauge	21mil, 430g
Opacity	98.95%
pH Value	7.9
Color	L* = 97.9 a*=3.6, b*=-7.8
Fabric Weave	Oxford 2 over 1
Whiteness	≥120 (CIE)
Printer Ink/Compatibility	Encad; ColorSpan; Canon, Hewlett-Packard; Mimaki; Roland; and Epson Series Ultrachrome, K3, dye and pigment-based inks.
Software Settings	The coating on this product is engineered for better than 300% ink coverage. A Heavy Weight Coated, or Enhanced Matte paper setting is the appropriate starting point, however, we recommend that you try different settings to achieve optimum performance for your specific application. A customer ICC profile is the only way to ensure optimal results.
Color Matching	For the best and most consistent results, a profile should be created using an external color calibrator in conjunction with your RIP and/or color matching software.
Light Fastness	The fading time of ink jet ink is a direct result of the inks that you choose, as well as the environment where the print is displayed. All dye-based inks fade noticeably under direct sunlight and in interior applications where direct sunlight may fall on the image, and/or, where fluorescent or other UV lighting is present. Although the fading process is inherent in all ink jet inks, certain UV enhanced inks, pigment-based inks, and UV inhibiting coatings will extend the longevity of ink color. Contact the ink manufacturer to determine a specific ink's suitability for a particular application.
Finishing/Post Processing	No post processing or finishing is required on this paper, however, a clear fixative may be applied to enhance certain areas of the print.
Optimal Service Environment	For printing: 68-77° F, 20-60% Relative Humidity. <b>For end use: 0-300° F</b>
Handling Recommendations	Due to the absorptive nature of the coating, you should avoid touching the coated surface of the paper. It is always recommended that cotton gloves be used when handling ink jet coated materials. Rolls of LexJet Sunset media are supplied with the coated side facing out.
Ideal Storage Conditions	70°F (21°C); 50% R.H.; Store in original packaging; A controlled environment is recommended.
Shelf Life	Greater than 1 year from the LexJet ship date when stored in proper conditions.

**Product Performance & Suitability:** All of the descriptive information and recommendations for the use of LexJet products should be used only as a guide. Furnishing such information and recommendations shall in no event constitute a warranty of any kind by LexJet. All purchasers of LexJet products shall independently determine the suitability of the material for the purpose for which it is purchased. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor manufacturer shall be liable either in tort or in contract for any loss or damage, direct, incidental or consequential (including loss of profits or revenue) arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in agreement signed by officers of seller and manufacturer.